

Fixed Extinguishing Systems | Deluge and Preaction Systems | **Deluge Sprinkler Systems**

Model GY46X/46X-300, GY56X/56X-300, GY86X/86X-300 Deluge Valve

Product Description

Model No	Release Type	Valve Size		Rated Working Pressure		End Connection	Remarks
		in	(mm)	psi	(kPa)		
GY46X	Electric	2, 2 1/2, 3, 4, 6, 8	(50, 65, 80, 100, 150, 200)	250	(1720)	Flange x Flange	a, b
GY46X-300	Electric	2, 2 1/2, 3, 4, 6, 8	(50, 65, 80, 100, 150, 200)	300	(2065)	Flange x Flange	a, b
GY56X	Electric	2, 2 1/2, 3, 4, 6, 8	(50, 65, 80, 100, 150, 200)	250	(1720)	Flange x Groove	a, b
GY56X-300	Electric	2, 2 1/2, 3, 4, 6, 8	(50, 65, 80, 100, 150, 200)	300	(2065)	Flange x Groove	a, b
GY86X	Electric	2, 2 1/2, 3, 4, 6, 8	(50, 65, 80, 100, 150, 200)	250	(1720)	Grove x Groove	a, b
GY86X-300	Electric	2, 2 1/2, 3, 4, 6, 8	(50, 65, 80, 100, 150, 200)	300	(2065)	Grove x Groove	a, b

Remarks:

a. Approved when supplied with a main control valve body ASTM A536 ductile iron, A351 CF8/CF8M Stainless Steel, B148 C95400/95800 Bronze.

b. Approved when equipped with a Confire Model CFU190525N solenoid valve. Rated Working Pressure of 300psi (2413 kPa) 24 V dc, 16 W, 1/2 in. NPT

Details

Category	Deluge Sprinkler Systems
Class of Work	1020 - Automatic Water Ctrl Valves
Approval Standard	FM 1020 - Automatic Water Control Valves
Certification Type	FM Approved

Listing Country: China

Cookies help us improve your website experience. By using our website, you agree to our use of cookies.

Company

Ningjin APC Industries Incorporated Company
 No 18 of Taishan Road, Ningjin, Shandong 253400, China
<http://www.apc-valve.com>

Confirm