

## Model GY46X-300

File Number: EX28916

### COMPANY

Ningjin APC Industries Incorporated Company

18 OF TAISHAN RD

NINGJIN, Shandong 253400 China

### MODEL INFO

GY46X-300

GENERAL						
Sprinkler System Type	Body Type	Nominal Pipe Size, NPS	End Configuration	Max Rated Pressure, psig (kPa)	Trim Configuration Type	Installed Position
Deluge sprinkler system	Globe	2, 2-1/2, 3, 4, 6, 8	Flanged	300 (2068)	Electric actuation, Manual actuation, Pneumatic actuation	Vertical, Horizontal

NOTES
<b>Additional Model Notes</b>
Flange Standard: ANSI Class300 or EN1092 PN25.

GENERAL
<b>Installation Limitations</b>
End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.
For accessories used with these valves, see certifications under Accessories for Special Systems (VLTR).
All trim configuration types shall include a manual release. Height of pilot line above valve limited as shown in the installation instructions.



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."